

Hazard Rating:  
4=extreme Fire = 1  
3=high Toxicity = 2  
2=moderate Reactivity = 1  
1=slight Special =  
0=insignificant

Emergency number 800-535-5053 or 352-323-3500

I. GENERAL INFORMATION

PRODUCT NAME : "Aldon SAME DAY SEALER"  
MANUFACTURER : Aldon Corporation  
DOT HAZARD CLASSIFICATION: Non Hazardous CHEMICAL FAMILY: Mixture  
EFFECTIVE DATE: 10/31/03

II. HAZARDOUS INGREDIENTS

MATERIAL	CAS#	AMOUNT	TLV
Water	7732-1805	>80	
Active Components*	Trade Secret	n/a	n/a

\*Specific chemical identities withheld as trade secret pursuant to OSHA regulations.

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.

III. PHYSICAL DATA

BOILING POINT (DEGREES F): Approx. 212 SPECIFIC GRAVITY (WATER=1): 1.03  
VAPOR PRESSURE(MM HG.) : 77 F 24 MM PERCENT VOLATILE : 96  
VAPOR DENSITY(AIR=1) : 1 EVAPORATION RATE (WATER=1): 1  
SOLUBILITY IN WATER : complete REACTIVITY IN WATER : none  
APPEAR.& ODOR : clear liquid, no odor PH : 12-13

IV. FIRE & EXPLOSION HAZARD DATA

FLASH POINT (TEST METHOD): Setaflash Closed Tester - no flash to 200 F  
FLAMMABLE LIMITS: LEL/UEL : not applicable  
AUTO IGNITION TEMPERATURE : not applicable  
EXTINGUISHING MEDIA : Foam, CO2, Dry Chemical, Water  
SPECIAL FIRE FIGHTING PROCEDURES: avoid contact with amphoteric metals  
UNUSUAL FIRE & EXPLOSION HAZARDS: contact with amphoteric metals (aluminum, zinc, etc.) may generate flammable gas.

V. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE OF PRODUCT OSHA TEV ACGTH TLV CARCINOGEN  
NE SEE SECTION II NONE

SYMPTOMS OF EXPOSURE AND ROUTES OF ENTRY:

Eyes: May cause serious injury, severe redness

Skin: May cause severe burns. Systemic injury possible.

FIRST AID

Eyes: Flush with water for 15 minutes. Consult a physician.

Skin: Flush with water. Remove contaminated clothing and footwear.

If irritation persists, get medical attention.

Ingestion: Give plenty of water. Seek immediate medical attention.

=====  
VI. REACTIVITY DATA  
=====

STABILITY: stable                      CONDITIONS TO AVOID: strongly acidic materials

INCOMPATIBILITY(MATERIALS TO AVOID): acidic materials

HAZARDOUS POLYMERIZATION: will not occur      MATERIALS TO AVOID:

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide on  
incineration.

=====  
VII. ENVIRONMENTAL PROTECTION PROCEDURES  
=====

SPILL RESPONSE: small spill- adsorb on clay or inert adsorbent

large spill- Dike area. Pump to suitable salvage container.

WASTE DISPOSAL METHOD: Neutralize with vinegar or dilute phosphoric acid.

Dispose of in accordance with Federal, State and  
local regulations.

=====  
VIII. SPECIAL PROTECTION INFORMATION  
=====

=====

EYE PROTECTION: Safety glasses      SKIN PROTECTION: rubber or vinyl gloves

RESPIRATORY PROTECTION (SPECIFIC TYPE): not normally required

VENTILATION RECOMMENDED: general

OTHER PROTECTION: none normally needed

=====  
IX. SPECIAL PRECAUTIONS  
=====

HYGIENIC PRACTICES IN HANDLING & STORAGE: Avoid contact with skin.

Do not store next to acidic materials

OTHER PRECAUTIONS: Keep from freezing.

DISPOSAL OF EMPTY CONTAINERS: Triple rinse empty containers before returning  
to vendor. Drum reconditioner or disposal in acceptable dump site. Caps  
and bungs should be placed on empty containers.

=====  
X. USER'S RESPONSIBILITY  
=====

=====

The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment.

=====

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.